



RUBBER BINDERS



Erapol Rubber Binders

These products have been designed as a low cost means of binding together reconstituted rubber to produce safety surfacing solutions for various applications.

Properties:

- MDI BASED
- SINGLE COMPONENT
- MOISTURE CURED
- **EASY TO USE**
- 100% REACTIVE



Applications Include:

- SPORT SURFACES
- PLAYGROUND SURFACES
- UNDERLAY FOR SYNTHETIC GRASS
- SHOCK ABSORBING PAVERS/MATS
- SUITABLE FOR COMPRESSION MOULDING
- ANTI FATIGUE FLOORING



Products:

		STANDARD GRADE	WINTER GRADE	SUMMER GRADE
PROPERTIES		EMD73RB	EMD76RB	EMD288RB
Viscosity	(@ 25°C/cps)	4700	3200	7200
Cure Time before use	(hrs*)	24	24	24








Tack Free Time:

		Material	Parts Per Hundred (pph)	Tack Free Time	
	A	Rubber	80	3.5 hours*	
		Erapol EMD73RB	20		

	Material	Parts Per Hundred (pph)	Tack Free Time	
D	Rubber	80	2 hours*	
В	Erapol EMD73RB	20		
	Water	0.35		







Erapol Topcoat:

Erapol Topcoat is used as a protective layer over the existing rubber binder surface. Typical applications are running tracks and sport surfaces.

- TWO COMPONENT
- SELF-LEVELLING
- LOW VISCOSITY
- MDI BASED









Sydney Head Office

2- 4 Green Street Banksmeadow NSW 2019 Australia P +61 2 9666 3788 F +61 2 9666 4805

Era Polymers Pty. Ltd. has a policy of continual improvement so please ensure you are in possession of the latest issue of the Product Information sheet for the products you are planning to use. Although every effort has been made to ensure the accuracy of the information contained herein, Era Polymers Pty. Ltd. gives no warranty that the information is accurate and shall under no circumstances be liable to any person if it is not. The customer must satisfy himself as to the suitability of any of Era Polymers Pty. Ltd. products for their requirements.









www.erapol.com.au